

SALAERA

Baldwin™ - Series **20410D** Digital Cooler

Sector: **ENVIRONMENTAL**

Sector: **INDUSTRIAL**

Perma Pure is now part of Salaera

OVERVIEW

The Baldwin™- Series digital 20410D thermo-electric coolers are a powerful combination of the proven track record of Baldwin™-Series classic coolers with a new digital control system. This combination ensures reliable performance for high flow rate, high ambient temperature, and high water volume applications.



KEY FEATURES

- Reliable, dedicated Digital Control System keeps your system operating efficiently
- Advanced P.I.D. control algorithm increases temperature control precision to maintain analysis accuracy
- Continuous display of temperature eliminates guesswork – a quick look tells it all
- Alarm outputs provide alarm interface capability for your data acquisition system as well as direct control of sample pumps
- Configurable for simple control of multiple sample streams
- Individual water slip sensors and alarm outputs safeguard against upset conditions
- Gas stream temperature output allows direct monitoring, eliminating guesswork
- 115 or 230 VAC models
- MODBUS for remote monitoring

All Baldwin™-Series coolers use thermo-electric elements (Peltiers) to cool the sample gas to the desired dew point temperature. Condensate can be removed as it forms by an available peristaltic pump.

ALL BALDWIN™– SERIES COOLERS INCLUDE:

- **Dependable Water Removal**
- ***Alarm Relays Protect Analyzers***
- **Low Maintenance**
- **EZ-Clean twist-apart impingers (Optional)**
- **Single or Dual Sample Streams**
- **Durinert-coated impingers (Optional)**

Learn more about our Baldwin™ Series Digital Cooler

Nafion™ and any associated logo is a trademark or copyright of THE CHEMOURS COMPANY FC, LLC USED UNDER LICENSE BY PERMA PURE LLC.

SALAERA

Sector: ENVIRONMENTAL

Sector: INDUSTRIAL

BALDWIN™ - SERIES 20410D DIGITAL COOLER

Specifications

Standard Capacity from 10 to 20 LPM	
Model	20410D
Standard Capacity	10-20 LPM (21-42 SCFH)
Impingers	Passive: 2 x 10 in Active: 2 x 10 in
Dimensions (H x W x D)	15 x 13 x 12 in (38 x 33 x 30 cm)
Weight	39 lbs (18 kg)

Performance Charts



Intelligent Product Numbering System

Follow the below 5 steps to determine your product number.

Step 1: Select Model (Required)	
20410D	**4C-20410D**
Step 2: Select Voltage (Required)	
115 VAC, 50/60 Hz	**1A**
230 VAC, 50 Hz	**2A**
Step 3: Select Impingers (Required)	
10″ Stainless Steel, EZ Clean Twist-Apart Impingers	**ES**
10″ Glass Impingers, threaded with fittings	**G**
10″ Kynar Impingers	**K**
10″ Stainless-Durinert coated, EZ Clean Twist-Apart Impingers	**ED**
Step 4: Select NJ Thermocouple Option (Stainless Steel and Stainless-Durinert Coated Impingers Only)	
New Jersey thermocouple temperature sensor; lead wires only	**NJ**
Step 5: Select Water Slip Sensor Option	
Water slip sensor with inline flow holder; 1/4″ Kynar tube fittings	**WS**

Example Product Number

4C-20410D	1A	ES	NJ	WS
Cooler	Voltage	Impingers	NJ Thermocouple	Water Sensor

Nafion™ and any associated logo is a trademark or copyright of THE CHEMOURS COMPANY FC, LLC USED UNDER LICENSE BY PERMA PURE LLC.